MODY UNIVERSITY
OF SCIENCE AND TECHNOLOGY
LAKSHMANGARH * RAJASTHAN
A Leading Women's University

College of Engineering & Technology

Ph.D.

A
Comprehensive Report
On

ROBOTICS & WIRELESS SENSORS FOR DISASTER MANAGEMENT WITH HARDWARE IMPLEMENTATION

Submitted to:
Dr.A Senthil

Submitted by:
Savyasachi
(150443)

ROBOTICS & WIRELESS SENSORS FOR DISASTER MANAGEMENT WITH HARDWARE IMPLEMENTATION

Keywords: Disaster Management, Robot, Monitoring System, Wireless Sensor Network, Arduino Programming

1. INTRODUCTION

Over the inhale few ages, contemporary robots inserted by the entire of bunches of sensors and capacities are focus of fascination and consideration of specialists all from one end to the next the world. This paper depicts the survey and usefulness of a Robot that can be utilized as a part of circumstance of debacle administration to save human life. The robot is composed in an outstanding a procedure that it can be utilized by entire association for different reason. This robot acts as, certainty finding for living individuals and gathers information from the air. The group of safeguard individuals can remotely get the information progressively and play out their activity as needs be. By the assistance of this robot save group can pick up data that the way is protected or not before entering to that specific area. The robot is furnished with LPG gas module, climatic condition and dampness sensor light sensor, Magnetic field sensor, metal finder. It has a live camera that is furnished with two way sound correspondence, day and night vision. Camera gives live spilling immediately general remote connection at 2.4 GHz ISM band. Robot is having a most recent 18650 battery which can give energy to three hours at single charge.



FIG 1: GENERAL ARCHITECTURE OF ROBOT AND WIRELESS NETWORK

The Robot is furnished with both RF module and in addition Bluetooth module. Radio connection is utilized where imagine separate correspondence is required. It gives a range up

to 100 meters when worked at culminate control. Bluetooth Module gives consummate duplex method of correspondence for all that it gives run up to 20 meters. The Robot can be worked on any android gadget. Android elaborate gadget sets up association by the entire of robot through Bluetooth. every one of the readings from various sensors are appeared on android gadget. The administrator design of robot with various remote system is said in figure 1. To deal with robot through radio connection, a different remote is utilized. It has two diverse RF module timed at 315MHz and 433 MHz The two distinctive recurrence are utilized to stay away from the odds of entomb channel impedance. The interfacing of the diverse sensors is done through Arduino UNO board since Arduino is an open source microcontroller so change of robot is completely simple over any PC. The therefore areas depict the related work, Process stream Chart, mechanical engineering outline, Hardware design of the robot, equipment design of the collector and transmitter, route calculation, Sensor interfacing calculations, Android application for Robot control, synopsis lastly the conclusion.

2. LITERATURE REVIEW

Jeong Min Chae, et.al [1] portrayed that the HLA control a decent variety of capacity associated with cleared reaction and impact powerlessness to wherever 40 sicknesses. It is essential to discover and soon thereafter HLA cause the ailment or fix powerlessness or course of it. In this paper, they built up a programmed HLA-illness data extraction technique that utilizations biomedical productions. in the first place, HLA and maladies are notable in the writing utilizing worked in normal dialects and contamination classes of Mesh. second, Stephan Bosch, et.al [2] portrayed that self-supporting vehicles are utilized as a part of ranges dangerous to people, by the entire of altogether more noteworthy utility than the proportional, kept an eye on vehicles. This paper investigates the purpose of a planned group of self-ruling vehicles, commonly applications in helpful observation, mapping obscure territories, catastrophe administration or space investigation. Kamol Chuengsatiansup, et.al [3] suggested that Plasma-RX is an arrangement of robots for go with and safeguard mission in a urban situation. The robot setup contains differential drive tracks by the entire of front/raise flippers and serial-interface arms prepared by the entire of cameras.

Josh D. Freeman, et.al [4] depicted that over the previous decade, regular and human-instigated calamities have asserted a great many lives. productive robots prepared by the

entire of contemporary sensors and coordinating remote systems are drawing in consideration from analysts and rescuers all around the globe. Avgoustinos Filippoupolitis, et.al [5] demonstrates that clearing of a working amid a crisis circumstance, an outstanding as a fire, is a perplexing and testing errand. As the conditions wholesome the building change because of the spreading of the peril, it ends up noticeably troublesome for an evacuee to locate the magnificent departure way. P. Beckerle, et.al [6] depicted that paper presents a mechanical idea for the appraisal of mental factors in prosthetic plan. Its point is to take after the postural developments of the members while those are directing hunching down developments with a specific end goal to research the mix of manufactured appendages to the subject's body conspire. thusly, the robot imitates the usefulness and perspective of the human foot, shank and thigh and additionally the lower leg and knee joint.

Tom Carlson, et.al [7] shows that paper we propose a system to change the level of assistance gave by a typical controller, given the natural setting, and per the setting of the customer's available lead. Helge-Björn Kuntze, et.al [8] exhibits that the made social requests have an unusual condition of availability for normal or man-made fiascoes. Regardless, such events can't be completely foreseen, and when a scene like a seismic tremor or an incident in a blend or nuclear plant hits a populated district, spare gatherings ought to be used. In such conditions it is a requirement for shield gatherings to get an energetic framework of the situation in order to recognize possible regions of setbacks that ought to be spared and hazardous territories that ought to be secured. Michael Tornow, et.al [9] depicted that Mobile robots can help individuals in disaster organization or regular insight by building a multi robot gathering, filling in as an appropriated sensor performing craftsman system. Remembering the true objective to mastermind the operations of a multi robot assemble the human machine interface is required to translate orders which will potentially be performed by a substitute robot, e.g. showing a domain to be separated.

Yusuf Çeri, et.al [10] depicted that survey intends to set up an alternative correspondence orchestrate which enables protect gathering to talk with each other and disaster setbacks if there ought to be an event of a phone sort out breakdown or over-trouble in a calamitous occasion, for instance, tremor or whirlwind. Kapil D. Katyal, et.al [11] suggested that present personality PC interface (BCI) control of exceedingly talented mechanical controllers and prosthetic devices commonly depend completely on neural interpret counts to choose the customer's arranged development. Seigi Matsumoto, et.al [12] portrayed that correct now,

numerous examinations are being done on mobile phone based catastrophe correspondence structures. Regardless, most existing structures acknowledge that each required application are presented in the phones of all individuals already the disaster happens, which is far-fetched in genuine catastrophe circumstances.

Charilaos Stais, et.al [13] exhibits that get-together information profitably from a, maybe isolated, sensor organize presents a critical issue in a disaster recovery applications. Unless a transmission control segment exists, a sink can be flooded with information sent by sensors, or sensor transmissions may be lost on their way to the sink. Along these lines, there is a requirement for a strong tradition that normally and rapidly acclimates to hardships, stop up and framework changes due to sink flexibility. Wen Yen Lin, et.al [14] depicted for the headway of IPv6 related applications, organizations association and up-grades, We propose an emergency correspondence APP using the Wi-Fi Ad hoc structure and IPv6 mastermind . Clarence W. de Silva, et.al [15] proposed there are various usages of multi-robot support. They consolidate fabricating plant floor, emergency response and shield, homecare, normal resource checking, and outdoors mechanical operations, for instance, accuse examination and repair.

Jiao Wang, et.al [16] depicted that driver-vehicle systems, the Human-Machine Interface (HMI) expect an imperative part to help the drivers in understanding the status of the vehicle and besides fills in as a data device. The HMI is an essential part in different levels of free driving. Sooyong Lee, et.al [17] proposed For robot teleoperation, an impressive measure of investigates have been done to control the slave robot from remote site using an expert arm. To impact the expert to feel an indistinct power from the slave robot, constrain feedback is fundamental for correct control overseeing dark circumstances. Liam Pedersen, et.al [18] delineated that future watched out for examination will incorporate logically complex missions in space and on planetary surfaces. Flight groups ought to be for the most part sure about routine operation with ground reinforce giving brisk ace gathering and extraordinarily named offer assistance. Making and executing such control techniques requires machine understanding, coupled solidly with human learning, to twist up detectably a vital bit of future flight systems for both watched out for and unmanned missions. David I. Gertman, et.al [19] show availability for engineered, natural, and radiological/nuclear scenes at nuclear power plants (NPPs) fuses the association of all around arranged emergency response gatherings. While bunches are required to do well, data from various ranges suggests that the

accommodation and precision related with scene response can be upgraded through shared human-mechanized affiliation.

Ko, Daesik, et.al [20] portrayed that the possibility of the u-City is the future city exhibit in light of urban progressions which fuse urban organization, life quality change, new current change, et cetera. Likewise, it includes three parts – development, space, lifestyle. Jae Weon Hong, et.al [21] depicted that this examination attempts to uncover knowledge into the components that effect the zones of bank workplaces in setting up a bank's office compose from the edge of the framework examination. While the past examinations separated the zones of bank workplaces on the commence of their geographical qualities and picture, the criticalness of this examination rests upon it endeavors to explore the region factors from another perspective of the improvement method for budgetary customers.

Kwak, Youngsik, Lee, et.al [22] shows that paper hopes to propose a sweeping esteeming schemata that item specialists, vendors, and distributers can use paying little regard to the state of programming jobs. Zhen-jie Jiang, et.al [23] depicted that Thanks to its immense motivation in Anti-dry season, Sabina vulgaris is twisting up progressively basic. Regardless, a considerable amount of past research work was chiefly based on its eco-physiological properties while neglecting its fundamental topological outline and improvement rules. Tune Xiao-feng, et.al [24] suggested that SVM for arrange is sensitive to noise and multicollinearity between qualities. Correlative part examination (CCA) was used to executed multi collinearity and confusion of one of a kind example data before described by SVM.

Liangjiang Wang, et.al [25} depicted that new machine learning approach has been made in this examination for game plan based desire of DNA-limiting developments in proteins. The approach used both the checked data cases accumulated from the open structures of protein-DNA buildings and the rich unlabeled data found in protein progression databases. Yeongjoon Gil, et.al [26] portrayed that the psyche is dealing with various acts and considerations of individuals. Among the components of the cerebrum, essential initiative, considering and complex calculation are spoken to by the frontal fold. If the FLA(Frontal Lobe Activity) is kept low for a drawn out extend of time, human considering and fundamental authority are ruined and unfriendly to social practices can rise which are not by any stretch of the imagination sensible in context of normal residents and it can achieve significant issues.

Yushi Zhang, et.al [27] shows that solid voice based features for biometric check in rambunctious conditions are proposed. The proposed getting ready joins Gammatone sound-related bandpass filtering of talk banner, revision, and strain to show the effects of the sound-related system edges. Three features are expelled by applying Independent Component Analysis to the repeat, cepstral and auto-correlogram zones of the stuffed yield signals separately. Jianhua Dai, et.al [28] depicted that this paper, 2-sort out Radial Basis Function (RBF) Network methodology is used for neural spike orchestrating. Immediately, unrefined signs are obtained from Neural Signal Simulator, and included redundant sound from - 10dB to - 40dB. Likewise, spikes are recognized out with facilitated channel from signals. At long last, 2-compose RBF frameworks are constructed and the spikes are orchestrated using RBF frameworks. The examinations exhibit that 2-compose RBF orchestrate is an effective mechanical assembly for neural spike masterminding.

A. Taleei, et.al [29] proposed that Microsatellites have pushed toward getting to be markers of choice for sub-nuclear mapping and marker helped assurance of key attributes, for instance, illness protection in numerous item species. Ying Sun , et.al [30] shows that this paper, a novel help vector batching count in perspective of k-suggests (SVC-KM) is presented improve the SVC running pace, and additionally beat the deficiencies of k-infers computation. Immediately, SVC estimation was used to recognize a couple of examples as inconsistencies and some others as intra-gather centers, with the objective that it ousted uproar and expelled illustrations near the pack focus. Shaikh Muhammad Allayear, et.al [31] delineated that paper we have proposed a parameter surveyed iSCSI tradition that robotizes the multi authority coordination on the advantage obliged contraptions for the human administrations advantage. The coordination between the benefit control contraptions and modernized authorities are kept up by a two-way handshaking mode iSCSI with some surveyed parameters.

3. CONTRIBUTION & RESEARCH GAP

PIR sensor in robot is utilized to distinguish the people. The PIR sensor is only unfeeling Infra-Red sensor. These sensors take a shot at the rule that they each human as transmits infra-red radiations of totally low wave length. in this way this sensor detects these radiations and yields a rationale profitable esteem. This sensor gave a pink slip sense the human inside

the scope of 20feet. They have a connected with voltage of 2.2-5V. PIR sensor is available by PC to A3 stick of the microcontroller. This work will be give better outcome to the catastrophe administration in the coming situation.

4. RESEARCH PLAN

This area will portray the equipment engineering of the robot that will be utilized by protect group amid calamities.

4.1. PLATFORM

The robot depends on an engine driver IC board mounted to a mechanical heavily clad work force bearer stage, with a specific end goal to empower it to go on harsh surface and on stairs. The stage comprises of six adapted DC engines whose apparatuses can be changed to control its energy and speed as per the necessity. The engine driving circuit can get input either straightforwardly from RF flag decoder or because of miniaturized scale controller board while working amid blue tooth interface.

4.1.1 HUMIDITY AND TEMPERATURE SENSOR

Mugginess and air condition Sensor DHT11 incorporates a resistive-sort dampness estimation segment and a NTC environmental condition estimation segment. It is associated with an important execution 8-bit microcontroller keeping in mind the end goal to offer great quality and in addition quick reaction. Each DHT11 sensor includes greatly precise alignment of mugginess adjustment chamber. The alignment coefficients put away in the OTP program memory, inward sensors identify motions simultaneously. The single-wire serial interface framework is coordinated to wind up plainly snappy and simple.

4.1.2 LPG AND SMOKE SENSOR

LPG and Smoke Sensor MQ5 is outstandingly sensitive towards methane, propane and butane. It contains SnO2. Right when SnO2 is warmed, O2 gas held at the surface and it

outlines a hindrance at the surface. Right when thickness is changed at the surface, the gas is recognized.

4.1.3 MAGNETIC FIELD SENSOR

It contains a vacuum tube having two metal plates. At whatever point the vacuum tube partner the two metal plates is experienced an alluring exacerbation, the two plates gets related. Due to this affiliation the present starts to stream and consequently the appealing field is recognized.

4.1.4 WIRELESS CAMERA

Remote camera used as a piece of this Robot is in a general sense an Internet tradition camera, or IP camera, which is a sort of automated camcorder typically used for perception. It can send and get data by methods for PC orchestrate and the Internet. The camera has Day and Night Vision and it can perceive development in 30 meter broaden. It involves two separate motors which engages it to give a planar vision of 360° and upward vision of 270°. Motor improvement of camera can be controlled remotely by Operator. It is furthermore equipped with two way solid correspondence module.

4.1.5 ULTRASONIC (UV) SENSORS OR ULTRASOUND SENSORS:

Bats are splendid creatures. Trance from the eyes however then a fantasy so correct that could perceive a moth and a broken leaf despite when flying at full speed. Probably the vision is more sharp than our own particular and is much past human capacities of seeing, yet is irrefutably not outside our capacity to fathom. Ultrasonic running is the strategy used by bats and various distinctive creatures of the arrangement of all creatures for navigational purposes. In an offer to mimic the techniques for nature to get an edge over everything, we individuals have fathomed it and have adequately imitated some of these signs and saddled their capacity to the best degree.

4.2 CONTRIBUTION

Contribution of this design is the wireless camera having both day and night vision and it can be operated through two different network running on two different ISM band since it is

equipped with both RF module as well as Bluetooth module for disaster management . Radio link is used where long distance communication is required. One of its best feature is that the Robot can be operated through any android device. So we think that this design is good and effective for rescue teams because it will give an overall picture about the dangerous elements that could exist in the affected area and also the robot will not be that expensive.

5. TRANSMITTER AND RECEIVER ARCHITECTURE

Transmitter: Transmitter circuit of robot is fundamentally remote of the robot which is worked by the client. The RF remote of robot contains two RF transmitters which transmit motion for two radio wires. It has two HT12E IC which encode motion as indicated by the address created by DP switches. In this circuit an outstanding of the HT12E IC is consider to encode information created by touch touchy key. These four touch delicate keys are utilized to control the development of robot. The other HT12E IC is utilized to encode the information produced by push keys. These keys are utilized to carry on the lights and arms of the robot.

OVERVIEW OF HUMAN-SENSING

Human-detecting is the way toward separating whole data with respect to the general population in some condition. In this review we have go for the induction of spatiotemporal property-Presence. nearness is apparently the property that is most by and large looked for after in existing certifiable applications, the most famous nearness sensor being movement sensors (PIR) and vicinity sensors (scalar infrared range-finders).At the least level, human-detecting is indistinguishable to measuring, either specifically or by implication, a notable or a greater amount of the horde ways people affect their surroundings. These are human characteristics that are either identified with human nearness or to human activities.

There are additionally some human attributes that can be abused in human-detecting frameworks, briefly depicting the present detecting modalities that can be utilized to quantify them. static attributes come from the physiological properties are delivered at all a man is available, regardless of what he or she is doing. normal static attributes are weight and state of which shape can be valuable for building up our framework. shape is measured in a roundabout way: has a section in indicators work by converging a man's shape by the entire of geometric lines which are either effectively created by the sensor itself (in the

circumstance of radars, for instance) or inactively appropriated from nature (e.g. cameras). accordingly, shape is a characteristic that expect be removed from a notable of three unmistakable qualities: reflectivity (with cameras or radars, for instance), constriction (tomographic sensors), or emissivity (warm imagers).

6. OBJECTIVES OF THE PROPOSED RESEARCH

- To show No death toll and property in the disaster management
- Easy clearing if there should be an occurrence of calamity
- To control Arduino robot by an advanced mobile phone.
- To compel in detecting moderation
- To Develop for a low-cost design implementation
- To Develop Natural Disaster Monitoring with Wireless Sensor Networks

Scope for Future Work

- The principle reason for the proposed framework is to distinguish individuals and give us data about their essence and area.
- Henceforth we can utilize GPS framework to know their correct area.
- For growing the extent of correspondence with the protect gathering, GSM module can be joined.
- Furthermore, metal and bomb locators can be used to keep up a vital separation from possible damage. Light-weighted daylight based sheets can be joined to make robot 'Self Charging'

7.ARDUINO SOFTWARE


Blink | Arduino 0021
Menu bar
File Edit Sketch Tools Help
Button bar
Blink
Blink
Turns on an LED on for one second, then off for one second, repeatedly
This example code is in the public domain.
*/
Input / Edit Area
void setup() {
// initialize the digital pin as an output.
// Pin 13 has an LED connected on most Arduino boards:
pinMode(13, OUTPUT);
}
void loop() {
digitalWrite(13, HIGH); // set the LED on
delay(1000); // wait for a second
digitalWrite(13, LOW); // set the LED off
delay(1000); // wait for a second
Done compiling.
Status bar
Program Notification Area
Binary sketch size: 1512 bytes (of a 126976 byte maximum)
19

Fig.2. ARDUINO SOFTWARE TOOL

7.1 Arduino Programming Basics Structure:

Each arduino program (frequently called a draw) has two required capacities (additionally called schedules). Void setup () {} All the code between the two wavy sections will be run once when your arduino program initially runs. Void circle () {} This capacity is pursued setup has wrapped up. After it has run once it will be run once more, and once more, until the point that power is expelled. Arduino is an open-source arrange used for building equipment wanders. Arduino includes both a physical programmable circuit board (oftentimes insinuated as a microcontroller) and a touch of programming, or IDE (Integrated Development Environment) that continues running on your PC, used to make and exchange PC code to the physical load up. The Arduino arrange has ended up being exceptionally outstanding with people just start with hardware, and in light of current conditions. Not in any way like most past programmable circuit sheets, the Arduino does not require an alternate piece of hardware (called a product build) remembering the true objective to stack new code onto the board – you can fundamentally use a USB link. Moreover, the Arduino IDE uses an enhanced variation of C++, making it less requesting to make sense of how to program. Finally, Arduino gives a standard shape factor that breaks out the components of

the littler scale controller into a more accessible package. The Uno is one of the more common sheets in the Arduino family and a mind blowing choice for youngsters.

8. SENSOR INTERFACING ALGORITHMS

Diverse sensors are interfaced with the Arduino Board. The idea behind using Arduino is that the structures like Arduino give sets of mechanized and basic I/O sticks in its IC with the objective that it can be interfaced to different extension sensors and diverse circuits. The Arduino board have feature like serial correspondences interfaces, including features like USB for stacking programs from PCs. IC like microcontrollers programming, the Arduino organize gives a planned headway condition (IDE) in light of the Processing wander, that fuses support for C and C++ programming vernaculars additionally.

9. RESEARCH PLAN & EXPECTED OUTCOME

In result the essentialness delivered by the sensor furthermore increases. Proper banner embellishment circuits change over the imperativeness created by the sensor to a sensible voltage yield. In clear words the yield of a PIR sensor module will be HIGH when there is development in its field of view and the yield will be LOW when there is no development

Proposed Flow Chart



Fig.3. PROPOSED FLOW CHART

REVIEW OF HUMAN-SENSING

Human-detecting is the way toward extricating any data in regards to the general population in some condition. In this overview we have concentrated on the induction of spatio-transient property-Presence. Nearness is seemingly the property that is most regularly looked for after in existing true applications, the most prominent nearness sensor being movement sensors (PIR) and vicinity sensors (scalar infrared range-finders).At the least level, human-detecting is proportionate to measuring, either straightforwardly or in a roundabout way, at least one of the bunch ways people affect their surroundings. These are human attributes that are either identified with human nearness or to human activities.

There are additionally some human qualities that can be misused in human-detecting frameworks, quickly portraying the current detecting modalities that can be utilized to gauge them. Static characteristics come from the physiological properties are created at whatever point a man is available, regardless of what he or she is doing. Basic static attributes are weight and state of which shape can be helpful for building up our framework. Shape is measured in a roundabout way: shape identifiers work by crossing a man's shape with geometric lines which are either effectively created by the sensor itself (on account of radars, for instance) or inactively appropriated from the earth (e.g. cameras). Consequently, shape is an attribute that must be extricated from one of three different qualities: reflectivity (with cameras or radars, for instance), weakening (tomographic sensors), or emissivity (warm imagers).

Another static characteristic is the automatic movement of inside organs, for example, the heart and lungs. This can be measured through skin-entering radio and ultrasound signals. At last, a generally new road for human-detecting lies in fragrance discovery [Pearce et al. 2006].

Moreover, CO2 levels have likewise been utilized to identify the nearness of individuals, yet with moderate reaction times [De Cubber and Marton 2009].

Dynamic attributes are those that emerge from human movement. We separate these into three classes: outer movement, walk, and vibrations. Concerning vibrations, these are the weight waves that individuals deliver either automatically (as sounds and vibrations from strides, for instance) or deliberately (as discourse), which can be measured with accelerometers and receivers, separately.

REFERENCES

1. J. Min Chae, K. Park, Y.H. Jung, S.Y. Jung, JiEun C. and H. Bum Oh," "HaDextract : Extracting HLA-Disease Interaction Information from Biomedical Literature", International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2/08

2. S. Bosch, M. Marin-Perianu, R.Marin-Perianu, H. Scholten and P. Havinga, "Follow Me! Mobile Team Coordination in Wireless Sensor and Actuator Networks" 978-1-4244-3304-9/09

3. K. Chuengsatiansup, K.Sajjapongse, P. Kruapraditsiri, C. Chanma, N. Termthanasombat, Y. Suttasupa, S. Sattaratnamai, E. Pongkaew, P. Udsatid, B. Hattha, P. Wibulpolprasert, P.Usaphapanus, N. T.Manop Wongsaisuwan , W. Wannasuphoprasit, and P. Chongstitvatana, "Plasma-RX: Autonomous Rescue Robots", International Conference on Robotics and Biomimetics, 978-1-4244-2679-9

4. Josh D. Freeman, V. Omanan, and M.V. Ramesh, "Wireless Integrated Robots for Effective Search and Guidance of Rescue Teams", 978-1-4577-0261-7

5. A. Filippoupolitis, G. Gorbil and E. Gelenbe", "Spatial Computers for Emergency Management", IEEE Conference on Self-Adaptive and Self-Organizing Systems Workshops, 978-0-7695-4545-5

6. P. Beckerle, O. Christ, J. Wojtusch, J. Schuy, K. Wolff, S. Rinderknecht, J. Vogt, and O. von Stryk", "Design and Control of a Robot for the Assessment of Psychological Factors in Prosthetic Development", IEEE International Conference on Systems, Man, and Cybernetics, 978-1-4673-1714-6

7. T. Carlson, R. Leeb, R. Chavarriaga and J.del R. Mill´an", "Online Modulation of the Level of Assistance in Shared Control Systems", IEEE International Conference on Systems, Man, and Cybernetics, 978-1-4673-1714-6

8. H.Kuntze, C. W. Frey, I. Tchouchenkov, B. Staehle,Erich Rome, K. Pfeiffer, A. Wenzel, J. Wöllenstein,"SENEKA - Sensor Network with Mobile Robots for Disaster Management", 978-1-4673-2709-1

9. M. Tornow, A. Al-Hamadi and V. Borrmann", "Gestic-Based Human Machine Interface for Robot Control", IEEE International Conference on Systems, Man, and Cybernetics, 978-1-4799-0652-9

10. Y. Çeri, Yrd . Doç. Dr. Ali Gülbağ, "Afet Durumlarinda Akilli Cihazlarla Alternatif Haberleşme Sistemi Kurulmasi Establishing An Alternative Communication Network In Disaster Situations Using Smart Devices", IEEE Signal Processing and Communications Applications Conference, 978-1-4799-4874-1

11. K.D. Katyal, M. S. Johannes, S. Kellis, T.Aflalo, C. Klaes, T. G. McGee, M. P. Para, Y. Shi, B.Lee, K. Pejsa, C.Liu, B.A. Wester, F. Tenore, J. D. Beaty, A. D. Ravitz, R. A. Andersen, and M. P. McLoughlin", "A Collaborative BCI Approach to Autonomous Control of a Prosthetic Limb System", IEEE International Conference on Systems, Man, and Cybernetics, 978-1-4799-3840-7

12. S. Matsumoto, Y. Arakawa, E. Marko Trono, and K. Yasumoto", "RecureShare - Internet-less application distribution mechanism for internet-less emergency communication systems", International Workshop on Pervasive Networks for Emergency Management, 2015, 978-1-4799-8425

13. C. Stais and G.Xylomenos", "RT-SENMOS: Reliable Transport for Sensor Networks with Mobile Sinks", IEEE International Workshop on Distributed Mobile Systems & Services, 978-1-4673-7194-0

14. W. Yen Lin, K-Po Hsueh, P-Shan Pa", "The Development of Emergency Communication APP Using Ad Hoc Network with IPv6", International Conference on Intelligent Information Hiding and Multimedia Signal Processing, 978-0-7695-5668-0

15. C. W. de Silva, "Some Issues and Applications of Multi-robot Cooperation", International Conference on Computer Supported Cooperative Work In Design", 978-1-5090-1915-1

16. J. Wang, D. S¨offker", "Improving driving efficiency for hybrid electric vehicle with suitable interface", International Conference on Systems, Man, and Cybernetics, 978-1-5090-1897-0

17. S. Lee, J. Lee, M. Kim, C.-W. Lee", "A New Masterarm for Man-Machine Interface"

18. L. Pedersen and R. Brummett", "Collaborative Decision Systems Project Summary of Technology Developments for Human-Robotics Interactions", International Conference on Space Mission Challenges for Information Technology, 0-7695-2644-6

19. D. I. Gertman, D. J. Bruemmer, and R. Scott Hartley", "Improving Emergency Response and Human-Robotic Performance", IEEE HFPP, 1-4244-0306-5

20. K., Daesik, Park, and J. hong", "A Study on the development of customer-oriented u-City Service Model for u-City Business", International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2

21. J. Weon Hong, W.E. Hong, and Y. S. Kwak", "The Study of Location Strategy for Bank's Branch Network through the Analysis of Inter-regional Financial Transaction Network", International Conference on Future Generation Communication and Networking,

22. K.wak, Y.sik, Lee, Y.yung, and K. Yoonsik", "The Development of Software Pricing Schemata and Its Application to Software Industry in Korea", International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2

23. Z.-jie Jiang, Z.-feng Geng,W.-h. Zhou", "A Dynamic, Architectural Model of Sabina vulgaris Growth", International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2

24. Xiao-feng , Saman K Halgamuge, CHEN De-zhao, and HU Shang-xu"," Communication and Networking" "International Conference on Future Generation Communication and Networking", 978-0-7695-3431-2

25. L. Wang", "Random Forests for Prediction of DNA-Binding Residues in Protein Sequences Using Evolutionary Information", International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2

26. Y. Gil, S. Seo and J.Lee", "EEG Analysis of Frontal Lobe Activities by Decision Stimuli", International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2

27. Y. Zhang, W. H. Abdulla", "International Conference on Future Generation Communication and Networking", International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2.

28. J. Dai, X. Liu, S. Zhang, H. Zhang, Yu Yi, and X. Zheng, "Neuronal Spike Sorting based on 2-stage RBF Networks", International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2

29. A. Taleei, H. Kanouni, M. Baum, S.A. Peyghambari, S.M. Okhovat5 and M. Abang", "Identification And Mapping Of Qtls For Resistance To Ascochyta Blight (Pathotype Iii) In Chickpea", International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2

30. Y. Sun, Y. Wang, J. Wang, W. Du, C. Zhou", "A Novel SVC Method based on K-means",International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2

31. S. M. Allayear and S.S. Park", "An Evaluated iSCSI Protocol for an Embedded Multi-Agent Based Health Care Service", International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2

32. E. Wijaya, H. Harada and P. Horton", "Modeling The Marginal Distribution of Gene Expression with Mixture Models", International Conference on Future Generation Communication and Networking, 978-0-7695-3431-2